


SAW Bandpass Filter F2G1A



Features

- RF bandpass filter
- High attenuation
- No matching single-ended operation
- Ceramic Surface Mounted Device Package (3.0 mm × 3.0 mm)
- RoHS Compliant

Package Dimension – SMD 3.0 × 3.0



Dimensions shown are nominal in millimeters

Body : Al₂O₃ Ceramic

Lid : Kovar, Ni Plated

Terminations : Au plating 0.3 ~ 1.0 um, Over a 1.27 ~ 8.89 um
Ni Plating

Pin Configuration

2	Input
5	Output
1, 3, 4, 6	Case ground

Maximum Ratings

Parameter	Unit	Minimum	Typical	Maximum
Operating Temperature Range	℃	-30	25	80
Storage Temperature Range	℃	-40	25	85
Power Handling Capability	dBm	-	-	10

Electrostatics Sensitive Device (ESD)

SAW Bandpass Filter F2G1A



Specifications

$F_c = 2160 \text{ MHz}$

	Minimum	Typical	Maximum	Unit
Center Frequency (F_c)	-	2160	-	MHz
Insertion Loss (In $F_c \pm 10 \text{ MHz}$)	-	2.0	3.5	dB
Amplitude Ripple (In $F_c \pm 10 \text{ MHz}$)	-	0.2	2.0	dBp-p
VSWR (In $F_c \pm 10 \text{ MHz}$)	-	1.3	2.3	
Relative Attenuation				
DC ~ 500 MHz	21	39	-	dB
500 ~ 1900 MHz	20	35	-	
1900 ~ 2050 MHz	25	38	-	
2050 ~ 2090 MHz	30	35	-	
2240 ~ 2300 MHz	20	49	-	
2300 ~ 3000 MHz	22	29	-	
Input/Output Impedance		50		Ohms

Notes :


- 1) All specifications are based on the matching schematic shown below, measured by Agilent Network analyzer and full 2 port calibration.
- 2) Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances

SAW Bandpass Filter F2G1A



Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



Marking Configuration

1)
●
I²⁾
2G1A³⁾

1) Pad Number 1 Index

2) Manufacturer name



3) Marking Number

* Ink or Laser Marking available

SAW Bandpass Filter F2G1A





Typical Performance (at 25°C)





SAW Bandpass Filter F2G1A



Input / Output VSWR Charts



Input / Output Smith Charts




SAW Bandpass Filter F2G1A




Packing Specification

1. Reeling Quantity : 1000 pcs / reel
2. Taping Structure : The tape shall be wound around the reel in the direction shown below.



Tape Specification

1. Leader part and vacant position specification




2. Tensile strength of carrier tape

4.4N/mm width

3. Top cover tape adhesion


- 1) pull off angle : 0~15°
- 2) speed : 300mm/min
- 3) force : 20~70g



SAW Bandpass Filter F2G1A




Carrier Tape Dimensions [unit : mm]



A	3.40 ± 0.1
B	3.40 ± 0.1
C	7.25 ± 0.1
D	1.70 ± 0.1
E	12.00 ± 0.1
F	8.00 ± 0.1

Part Direction



Reel Dimensions [unit : mm]

