


SAW Bandpass Filter F2G51



Features

- RF bandpass filter
- High attenuation
- No matching single-ended operation
- Ceramic Surface Mounted Device Package (3.0 mm × 3.0 mm)
- RoHS Compliant

Package Dimension – SMD 3.0 × 3.0



Dimensions shown are nominal in millimeters

Body : Al₂O₃ Ceramic

Lid : Kovar, Ni Plated

Terminations : Au plating 0.3 ~ 1.0 um, Over a 1.27 ~ 8.89 um
Ni Plating

Pin Configuration

2	Input
5	Output
1, 3, 4, 6	Case ground

Maximum Ratings

Parameter	Unit	Minimum	Typical	Maximum
Operating Temperature Range	℃	-35	25	85
Storage Temperature Range	℃	-40	25	85
Power Handling Capability	dBm	-	-	10

Electrostatics Sensitive Device (ESD)

SAW Bandpass Filter F2G51



Specifications

$F_c = 2535 \text{ MHz}$

Terminating source impedance : 50Ω

Terminating load impedance : 50Ω

	Minimum	Typical	Maximum	Unit
Center Frequency (F_c)	-	2535	-	MHz
Insertion Loss (In $F_c \pm 35 \text{ MHz}$)	-	2.2	3.6	dB
Amplitude Ripple (In $F_c \pm 35 \text{ MHz}$)	-	0.8	2.2	dBp-p
VSWR (In $F_c \pm 35 \text{ MHz}$)	-	2.0	2.3	
Relative Attenuation				
DC ~ 2100 MHz	25	31	-	dB
2100 ~ 2400 MHz	27	34.5	-	
2650 ~ 3000 MHz	30	38	-	
Input/Output Impedance		50		Ohms

Notes :


- 1) All specifications are based on the matching schematic shown below, measured by Agilent Network analyzer and full 2 port calibration.
- 2) Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances

SAW Bandpass Filter F2G51



Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



Marking Configuration

1)
●
I²⁾
2G51³⁾

1) Pad Number 1 Index

2) Manufacturer name



3) Marking Number

* Ink or Laser Marking available

SAW Bandpass Filter F2G51





Typical Performance (at 25°C)





SAW Bandpass Filter F2G51



Input / Output VSWR Charts



Input / Output Smith Charts




SAW Bandpass Filter F2G51




Packing Specification

1. Reeling Quantity : 1000 pcs / reel
2. Taping Structure : The tape shall be wound around the reel in the direction shown below.



Tape Specification

1. Leader part and vacant position specification



2. Tensile strength of carrier tape


4.4N/mm width

3. Top cover tape adhesion

1) pull off angle : 0~15°

2) speed : 300mm/min


3) force : 20 ~ 70



SAW Bandpass Filter F2G51




Carrier Tape Dimensions [unit : mm]



A	3.40 ± 0.1
B	3.40 ± 0.1
C	7.25 ± 0.1
D	1.70 ± 0.1
E	12.00 ± 0.1
F	8.00 ± 0.1

Part Direction



Reel Dimensions [unit : mm]

