


SAW Bandpass Filter F2G63



Features

- RF Bandpass Filter
- No impedance matching require for operation at 50 Ω
- Ceramic Surface Mounted Device Package (3.0 mm * 3.0 mm)
- Single-ended Operation
- RoHS Compliant

Package Dimensions



Dimensions shown are nominal in millimeters

Body : Al₂O₃ Ceramic

Lid : Kovar, Ni Plated

Terminations : Au plating 0.3 ~ 1.0 μ m, Over a 1.27 ~ 8.89 μ m
Ni Plating

Pin Configurations

2	Input
5	Output
1, 3, 4, 6	Case ground

Maximum Ratings

Parameters	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-40	25	85
Storage Temperature Range	°C	-40	25	85
Power Handling Capability	dBm	-	-	15

Electrostatics Sensitive Device (ESD)

SAW Bandpass Filter F2G63



Specifications

$F_c = 2655 \text{ MHz}$

	Minimum	Typical	Maximum	Unit
Center Frequency (F_c)	-	2655	-	MHz
Insertion Loss (2620 ~2690 MHz)	-	2.2	3.6	dB
Amplitude Ripple (2620 ~2690 MHz)	-	0.7	2.2	dB
Group Delay Variation (2620 ~2690 MHz)	-	7	35	ns
VSWR (2620 ~2690 MHz)	-	1.9	2.5	
Relative Attenuation 300 ~ 500 MHz 500 ~ 2450 MHz 2450 ~ 2550 MHz 2745 ~ 3000 MHz	20 22 25 15	36 30 36 37	- - - -	dB
Input/Output Impedance		50		Ohms

Notes :


- 1) All specifications are based on the matching schematic shown below, measured by Agilent Network analyzer and full 2 port calibration.
- 2) Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
- 3) All attenuation measurements are measured relative to insertion loss

SAW Bandpass Filter F2G63



Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



Marking Configuration

1)
●

I²⁾

2G63³⁾

1) Pad Number 1 Index

2) Manufacturer name



3) Marking Number

* Ink or Laser Marking available

SAW Bandpass Filter F2G63





Typical Performance (at 25°C)





SAW Bandpass Filter F2G63



Input / Output VSWR Charts



Input / Output Smith Charts




SAW Bandpass Filter F2G63




Packing Specifications

1. Reeling Quantity : 3000 pcs / 13" reel (or 1000 pcs / 7" reel)
2. Taping Structure : The tape shall be wound around the reel in the direction shown below.



Tape Specification

1. Leader part and vacant position specification



2. Tensile strength of carrier tape


4.4N/mm width

3. Top cover tape adhesion

1) pull off angle : 0~15°

2) speed : 300mm/min


3) force : 20~70g



SAW Bandpass Filter F2G63




Carrier Tape Dimensions [unit : mm]



A	3.40 ± 0.1
B	3.40 ± 0.1
C	7.25 ± 0.1
D	1.70 ± 0.1
E	12.00 ± 0.1
F	8.00 ± 0.1

Part Direction



Reel Dimensions [unit : mm]

