


SAW Bandpass Filter F2G37



Features

- RF Bandpass Filter
- No impedance matching require for operation at 50 Ω
- Ceramic Surface Mounted Device Package (3.0 mm * 3.0 mm)
- Single-ended Operation
- RoHS Compliant

Package Dimensions



Dimensions shown are nominal in millimeters

Body : Al_2O_3 Ceramic

Lid : Kovar, Ni Plated

Terminations : Au plating 0.3 ~ 1.0 μm , Over a 1.27 ~ 8.89 μm
Ni Plating

Pin Configurations

2	Input
5	Output
1, 3, 4, 6	Case ground

Maximum Ratings

Parameters	Unit	Minimum	Typical	Maximum
Operating Temperature Range	$^{\circ}\text{C}$	-5	25	55
Storage Temperature Range	$^{\circ}\text{C}$	-30	25	85
Power Handling Capability	dBm	-	-	10

Electrostatics Sensitive Device (ESD)

SAW Bandpass Filter F2G37



Specifications

$F_c = 2350$ MHz

	Minimum	Typical	Maximum	Unit
Center Frequency (F_c)	-	2350	-	MHz
Insertion Loss (2300 ~2400 MHz)	-	3.0	3.5	dB
Amplitude Ripple (2300 ~2400 MHz)	-	1.5	3.0	dB
VSWR (2300 ~2400 MHz)	-	2.2	2.5	
Relative Attenuation				
0.3 ~ 2050 MHz	23	28	-	dB
2050 ~ 2170 MHz	30	32	-	
2170 ~ 2250 MHz	24	40	-	
2450 ~ 2550 MHz	18	38	-	
2550 ~ 3000 MHz	27	31	-	
Input/Output Impedance		50		Ohms

Notes :


- 1) All specifications are based on the matching schematic shown below, measured by Agilent Network analyzer and full 2 port calibration.
- 2) Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
- 3) All attenuation measurements are measured relative to insertion loss

SAW Bandpass Filter F2G37



Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



Marking Configuration

1)
●
I²⁾
2G37³⁾

1) Pad Number 1 Index

2) Manufacturer name



3) Marking Number

* Ink or Laser Marking available

SAW Bandpass Filter F2G37





Typical Performance (at 25°C)





SAW Bandpass Filter F2G37



Input / Output VSWR Charts



Input / Output Smith Charts




SAW Bandpass Filter F2G37




Packing Specifications

1. Reeling Quantity : 3000 pcs / 13" reel (or 1000 pcs / 7" reel)
2. Taping Structure : The tape shall be wound around the reel in the direction shown below.



Tape Specification

1. Leader part and vacant position specification



2. Tensile strength of carrier tape


4.4N/mm width

3. Top cover tape adhesion

1) pull off angle : 0~15°

2) speed : 300mm/min


3) force : 20~70g



SAW Bandpass Filter F2G37




Carrier Tape Dimensions [unit : mm]



A	3.40 ± 0.1
B	3.40 ± 0.1
C	7.25 ± 0.1
D	1.70 ± 0.1
E	12.00 ± 0.1
F	8.00 ± 0.1

Part Direction



Reel Dimensions [unit : mm]

