


SAW Bandpass Filter 222002B



1. Features

- IF bandpass filter
- High attenuation
- Single-ended operation
- DIP Package
- Maximum Storage Temperature Range : -40 °C ~ 85 °C
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D2012

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

SAW Bandpass Filter 222002B



3. Specifications

F₀ = 60.0 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	-	60.0	-
Insertion Loss	dB	-	24.0	26.0
1dB Bandwidth	MHz	-	20.2	-
3dB Bandwidth	MHz	20.4	20.5	-
40dB Bandwidth	MHz	-	21.85	21.98
Amplitude Ripple (F ₀ +/- 9.75 MHz)	dB	-	0.7	1.0
Group Delay Variation (F ₀ +/- 9.75 MHz)	nsec	-	50	100
Absolute Delay	usec	-	2.41	-
Ultimate Rejection	dB	50	52	-
Temperature Coefficient of Frequency	ppm/°C	-	-72	-

Notes :


- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss

SAW Bandpass Filter 222002B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



$L1 = 270\text{nH}$, $L2 = 180\text{nH}$

$C1 = 3\text{pF}$

5. Marking Configuration

ITF¹⁾06A001²⁾

222002B³⁾

1) Manufacturer name



2) Lot Number

3) Part Number

SAW Bandpass Filter 222002B



6. Typical Performance (at +25°C)



SAW Bandpass Filter 222002B

